

December 23, 2024

Chris Roberts  
Mackin and Son Automotive, Inc.  
300 SE Hearthwood Boulevard  
Vancouver, WA 98684

RE: Final Air Discharge Permit for a New Auto Body Facility


Dear Mr. Roberts:

A final determination to issue Air Discharge Permit (ADP) 24-3678 has been completed for ADP application CL-3280 pursuant to Section 400-110(4) of the General Regulations for Air Pollution Sources of the Southwest Clean Air Agency (SWCAA). Public notice for ADP application CL-3280 was published in the permit section of SWCAA's website on October 31, 2024. SWCAA did not receive a request for a public comment period in response to the public notice and has concluded that significant public interest does not exist for this determination. Therefore, a public comment period will not be provided for this permitting action. Electronic copies of ADP 24-3678 and the associated Technical Support Document are available for public review in the "Recent Air Discharge Permits" section under the "Air Permits" link on SWCAA's website (<http://www.swcleanair.gov>). Original copies are enclosed for your files.

ADP 24-3678 may be appealed directly to the Pollution Control Hearings Board (PCHB) within thirty (30) days of receipt as provided in Revised Code of Washington (RCW) 43.21B.

If you have any questions or comments, or desire additional information, please contact me or Vannessa McClelland at (360) 574-3058, extension 129.

Sincerely,



Uri Papish  
Executive Director

UP:VM





**AIR DISCHARGE PERMIT  
24-3678**

**Issued: December 23, 2024**

**Mackin's Prairie Auto Body**  
11601 NE 126<sup>th</sup> Street, Vancouver, WA 98662

**SWCAA ID – 2816**

REVIEWED BY:

  
Clinton Lamoreaux, Chief Engineer



APPROVED BY:

  
Uri Papish, Executive Director

**TABLE OF CONTENTS**

1. Equipment/Activity Identification ..... 1

2. Permit Requirements..... 1

    Emission Limits ..... 1

    Operating Limits and Requirements ..... 2

    Monitoring and Recordkeeping Requirements ..... 3

    Emission Monitoring and Testing Requirements ..... 3

    Reporting Requirements ..... 4

3. General Provisions ..... 5

**1. Equipment/Activity Identification**

<b>ID No.</b>	<b>Equipment/Activity</b>	<b>Control Equipment/Measure</b>
1	Spray Booth #1 - Global Finishing Solutions	Filter bank – high efficiency filter media Ultra-low Sulfur Fuel (Natural Gas)
2	Spray Booth #2 - Global Finishing Solutions	Filter bank – high efficiency filter media Ultra-low Sulfur Fuel (Natural Gas)
3	Paint Mix Room - Global Finishing Solutions	None

**2. Permit Requirements**

The following tables detail the specific requirements of this Air Discharge Permit (ADP). In addition to the requirements listed below, equipment at this facility may be subject to other federal, state, and local regulations. The requirement number is identified in the left-hand column. The text of the requirement is contained in the middle column. The emission unit, equipment, or activity to which the requirement applies is listed in the right-hand column.

**Emission Limits**

<b>Req. No.</b>	<b>Emission Limits</b>	<b>Equipment/Activity ID No.</b>								
1.	<p>Emissions from the spray coating operations must not exceed any of the following:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th><b>Pollutant</b></th> <th><b>Emission Limit</b></th> </tr> </thead> <tbody> <tr> <td>Volatile Organic Compounds</td> <td>2.0 tpy</td> </tr> <tr> <td>Particulate Matter, PM<sub>10</sub>, PM<sub>2.5</sub> total</td> <td>0.06 tpy</td> </tr> <tr> <td>Toxic Air Pollutants</td> <td>SQER for each pollutant. Combined TAPs (not including acetone or other non-VOC TAPs) must not exceed the VOC emission limit established above</td> </tr> </tbody> </table> <p>The long-term emission limits are 12-month rolling sums calculated consistent with Section 6 of the Technical Support Document (TSD) for this ADP.</p>	<b>Pollutant</b>	<b>Emission Limit</b>	Volatile Organic Compounds	2.0 tpy	Particulate Matter, PM <sub>10</sub> , PM <sub>2.5</sub> total	0.06 tpy	Toxic Air Pollutants	SQER for each pollutant. Combined TAPs (not including acetone or other non-VOC TAPs) must not exceed the VOC emission limit established above	1 – 3
<b>Pollutant</b>	<b>Emission Limit</b>									
Volatile Organic Compounds	2.0 tpy									
Particulate Matter, PM <sub>10</sub> , PM <sub>2.5</sub> total	0.06 tpy									
Toxic Air Pollutants	SQER for each pollutant. Combined TAPs (not including acetone or other non-VOC TAPs) must not exceed the VOC emission limit established above									
2.	<p>Emissions from natural gas combustion must not exceed any of the following:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th><b>Pollutant</b></th> <th><b>Emission Limit</b></th> </tr> </thead> <tbody> <tr> <td>Nitrogen Oxides</td> <td>1.29 tpy</td> </tr> <tr> <td>Carbon Monoxide</td> <td>1.08 tpy</td> </tr> <tr> <td>Particulate Matter, PM<sub>10</sub></td> <td>0.10 tpy</td> </tr> </tbody> </table> <p>The long-term emission limits are 12-month rolling sums calculated consistent with Section 6 of the TSD for this ADP.</p>	<b>Pollutant</b>	<b>Emission Limit</b>	Nitrogen Oxides	1.29 tpy	Carbon Monoxide	1.08 tpy	Particulate Matter, PM <sub>10</sub>	0.10 tpy	1 – 2
<b>Pollutant</b>	<b>Emission Limit</b>									
Nitrogen Oxides	1.29 tpy									
Carbon Monoxide	1.08 tpy									
Particulate Matter, PM <sub>10</sub>	0.10 tpy									

<b>Req. No.</b>	<b>Emission Limits</b>	<b>Equipment/ Activity ID No.</b>
3.	Visible emissions from the spray booths must not exceed zero percent (0%) opacity for more than three (3) minutes in any one-hour period as determined in accordance with SWCAA Method 9.	1 – 3

### **Operating Limits and Requirements**

<b>Req. No.</b>	<b>Operating Limits and Requirements</b>	<b>Equipment/ Activity ID No.</b>
4.	Reasonable precautions must be taken at all times to prevent and minimize fugitive emissions from plant operations.	Facility-wide
5.	Operations that cause or contribute to a nuisance odor must use recognized good practice and procedures to reduce these odors to a reasonable minimum.	Facility-wide
6.	Emission units and activities identified in this ADP must be maintained and operated in total and continuous conformity with the conditions identified in this ADP. SWCAA reserves the right to take any and all appropriate action to maintain the conditions of this ADP, including directing the facility to cease operations until corrective action can be completed.	1 – 3
7.	Each pollution control device must be operated whenever the processing equipment served by that air pollution control device is in operation. Control devices must be operated and maintained in accordance with the manufacturer's specifications. Furthermore, air pollution control devices must be operated in a manner that minimizes emissions.	1 – 2
8.	All exhausts must be discharged vertically into the ambient air above the level of the building roof. Any device that obstructs or prevents vertical discharge is prohibited.	1 – 3
9.	All surface coating must be performed inside the spray booths, unless otherwise specified by SWCAA.	1 – 2
10.	A differential pressure gauge (digital or analog) must be installed and maintained to measure the pressure drop across the spray booth exhaust filter media.	1 – 2
11.	All containers for VOC containing materials must be kept securely closed with a lid in place except when in active use. Open containers for storage, transfer or disposal of VOC containing materials are prohibited. In addition, all VOC containing materials used to clean and/or flush spray equipment or lines during clean up must be collected and stored in a closed container.	Facility-wide
12.	All spray booth doors must remain closed during spray coating operations.	Facility-wide
13.	Spray application of coatings containing chromium, lead, manganese, nickel, or cadmium compounds at a concentration greater than 0.1% by weight is prohibited.	Facility-wide
14.	All spray painting must be performed with properly operating high transfer efficiency spray equipment including, but not limited to, spray guns with HVLP or air-assisted airless configurations.	Facility-wide

<b>Req. No.</b>	<b>Operating Limits and Requirements</b>	<b>Equipment/ Activity ID No.</b>
15.	The Global Finishing Solutions spray booths must be operated with properly fitted exhaust filters that are demonstrated to provide at least 98 percent capture of coating overspray as determined using ASHRAE Method 52.1 or an equivalent method approved by SWCAA, or the filters must be certified to ASHRAE MERV 14 or better. Where two or more layers of filters are used, the combined capture efficiency must be at least 98% or the combined filtration shall achieve a minimum MERV of 14.	1 – 2
16.	A sufficient quantity of replacement exhaust filters must be kept on site and readily available. Replacements of exhaust filters must be performed at the manufacturer's specified intervals or more frequent, as necessary.	Facility-wide
17.	Spray booth heaters must only be fired on natural gas.	1 – 2

### Monitoring and Recordkeeping Requirements

<b>Req. No.</b>	<b>Monitoring and Recordkeeping Requirements</b>	<b>Equipment/ Activity ID No.</b>
18.	Except for data logged by a computerized data acquisition system, each record required by this ADP must include the date and the name of the person making the record entry, at minimum. If a control device or process is not operating, a record must be made to that effect.	1 – 3
19.	All records required by this ADP must be kept for a minimum period of no less than three (3) years and must be maintained in a form readily available for inspection by SWCAA representatives.	1 – 3
20.	Excess emissions and upset conditions must be recorded for each occurrence.	Facility-wide
21.	For each product used or produced at the facility that contains VOC, HAP, or TAP, the Permittee must maintain purchase receipts for quantities, Safety Data Sheet (SDS) information, and Technical Data Sheets (TDS) in a readily accessible form.	1 – 3
22.	Spray coating operations must be monitored and recorded as follows: (a) Digital records for the Global Finishing Solutions spray booths indicating filter replacement and/or differential pressure must be available for review; (b) Spray coating material consumption must be recorded monthly; (c) The quantity and type of hazardous waste disposal must be recorded monthly; (d) Booth heater fuel consumption must be recorded monthly; and (e) Filter changes and maintenance activities must be recorded for each occurrence.	1 – 3

### Emission Monitoring and Testing Requirements

No emission monitoring or testing were required for the approved equipment cited in this ADP.

**Reporting Requirements**

<b>Req. No.</b>	<b>Reporting Requirements</b>	<b>Equipment/ Activity ID No.</b>
23.	Upset conditions must be reported to SWCAA as soon as possible after discovery by phone call or phone message, email, or fax. It is the Permittee's responsibility to verify that the upset conditions information was received.	Facility-wide
24.	Excess emissions must be reported to SWCAA as follows: (a) As soon as possible, but no later than twelve (12) hours after discovery for emissions that represent a potential threat to human health or safety; (b) As soon as possible, but no later than forty-eight (48) hours after discovery for emissions which the Permittee wishes to claim as unavoidable pursuant to SWCAA 400-107(1); and (c) No later than thirty (30) calendar days after the end of the month of discovery for all other excess emissions.	Facility-wide
25.	Deviations from permit conditions must be reported as soon as possible but no later than 30 days after the end of the month during which the deviation is discovered.	Facility-wide
26.	All air quality related complaints received by the Permittee must be reported to SWCAA within three (3) calendar days of receipt. Complaint reports must include the date and time of the complaint, the name and contact information (if available) for the complainant, the nature of the complaint, and any actions taken by the Permittee to address the complaint.	Facility-wide
27.	An annual emissions inventory report must be submitted to SWCAA by March 15 for emissions from the previous calendar year in accordance with SWCAA 400-105(1). Each report must contain, at a minimum, the following information: (a) The annual sum of emissions of NO <sub>x</sub> , CO, VOC, PM, PM <sub>10</sub> , PM <sub>2.5</sub> , SO <sub>2</sub> , TAPs, and HAPs; (b) The quantity of each spray coating product purchased (gallons or lbs); (c) The quantity and type of hazardous waste disposed; and (d) The amount of natural gas consumed.	1 – 3

Req. No.	Reporting Requirements	Equipment/ Activity ID No.
28.	<p>A written report must be submitted to SWCAA at least seven (7) calendar days prior to the use of any new product that contains VOCs, TAPs, or HAPs. The report must contain the following:</p> <ul style="list-style-type: none"> <li>(a) A description of the type of product (e.g., resin, paint, solvent, etc.), the Safety Data Sheets and Technical Data Sheets, and the location where the product will be used;</li> <li>(b) The date by which the Permittee intends to begin use of the product;</li> <li>(c) The amount (gallons or lbs) expected to be used;</li> <li>(d) A quantification of the change in VOC, HAP and TAP emissions from the use of the product; and</li> <li>(e) A summary of any applicable requirement that would apply as a result of the product.</li> </ul> <p>If use of the new product would cause any emission limit or SQER to be exceeded, the Permittee must submit an ADP application to SWCAA to request a revision to this ADP. The Permittee must not begin using the new product until a revised ADP is issued.</p> <p>Any new product that is only to be used for testing purposes with a quantity of five (5) gallons or less of usage does not need to be reported to SWCAA prior to use.</p>	1 – 3

### 3. General Provisions

Req. No.	General Provisions
A.	For the purpose of ensuring compliance with this ADP, duly authorized representatives of the Southwest Clean Air Agency must be permitted access to the Permittee's premises and the facilities being constructed, owned, operated and/or maintained by the Permittee for the purpose of inspecting said facilities. These inspections are required to determine the status of compliance with this ADP and applicable regulations and to perform or require such tests as may be deemed necessary.
B.	The provisions, terms, and conditions of this ADP bind the Permittee, its officers, directors, agents, servants, employees, successors and assigns, and all persons, firms, and corporations acting under or for the Permittee.
C.	The requirements of this ADP survive any transfer of ownership of the source or any portion thereof.
D.	This ADP must be posted conspicuously at or be readily available near the source.
E.	This ADP will be invalidated, in whole or in part, if construction or installation of any new or modified equipment has not commenced within eighteen (18) months from date of issuance, if construction is discontinued for a period of eighteen (18) months or more without prior SWCAA approval, or if construction is not completed within a reasonable time.



<b>Req. No.</b>	<b>General Provisions</b>
F.	This ADP does not supersede requirements of other agencies with jurisdiction and further, this ADP does not relieve the Permittee of any requirements of any other governmental agency. In addition to this ADP, the Permittee may be required to obtain permits or approvals from other agencies with jurisdiction.
G.	Compliance with the terms of this ADP does not relieve the Permittee from the responsibility of compliance with SWCAA General Regulations for Air Pollution Sources, previously issued Regulatory Orders, RCW 70A.15, Title 173 WAC or any other applicable emission control requirements, nor from the resulting liabilities and/or legal remedies for failure to comply.
H.	If any provision of this ADP is held to be invalid, all unaffected provisions of the ADP will remain in effect and be enforceable.
I.	No change in this ADP will be made or be effective except as may be specifically set forth by written order of the Southwest Clean Air Agency upon written application by the Permittee for the relief sought.
J.	The Southwest Clean Air Agency may, in accordance with RCW 70A.15, impose such conditions as are reasonably necessary to ensure the maintenance of compliance with the terms of this ADP, the Washington Clean Air Act, and the applicable rules and regulations adopted under the Washington Clean Air Act.
K.	For the purposes of establishing if a condition of this ADP has been violated or is being violated, nothing in this ADP precludes the use, including the exclusive use, of any credible evidence or information relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test procedures or methods had been performed.