

February 26, 2025

Mr. Guy Copenhaver, Manager Copenhaver Construction, Inc. 22393 State Route 2 East Creston, WA 99117

Subject: <u>Final Air Discharge Permit / Nonroad Engine Permit for New Rock Crushing and</u> <u>Screening Equipment</u>

Dear Mr. Copenhaver:

A final determination to issue Air Discharge Permit / Nonroad Engine Permit 25-3685 (ADP/NEP 25-3685) has been completed for ADP/NEP Application CO-1111 pursuant to Section 400-110(4) of the General Regulations for Air Pollution Sources of the Southwest Clean Air Agency (SWCAA). Public notice for ADP/NEP Application CO-1111 was published in the permit section of SWCAA's internet website on February 6, 2025. SWCAA did not receive a request for a public comment period in response to the public notice and has concluded that significant public interest does not exist for this determination. Therefore, a public comment period will not be provided for this permitting action. Electronic copies of ADP/NEP 25-3685 and the associated Technical Support Document are available for public review in the permit section of SWCAA's internet website (http://www.swcleanair.gov/permits/adpfinal.asp). Original copies are enclosed for your files.

This Air Discharge Permit may be appealed directly to the Pollution Control Hearings Board (PCHB) within 30 days of receipt as provided in RCW 43.21B.

If you have any comments, or desire additional information, please contact me or Wess Safford at (360) 574-3058, extension 126.

Sincerely, Uri Papish

Executive Director

UP:wls

Enclosure - ADP/NEP 25-3685 and Technical Support Document



AIR DISCHARGE PERMIT / NONROAD ENGINE PERMIT 25-3685

Issued: February 26, 2025

Copenhaver Construction 460 Kalama River Rd, Kalama, WA 98625

SWCAA ID - 2822



REVIEWED BY:

Clinton Lamoreaux, Chief Engineer

Uri Papish, Executive Director

APPROVED BY:

TABLE OF CONTENTS

Section	Page
1. Equipment/Activity Identification	1
2. Approval Conditions	1
Emission Limits	1
Operating Limits and Requirements	2
Monitoring and Recordkeeping Requirements	3
Emission Monitoring and Testing Requirements	4
Reporting Requirements	4
3. General Provisions	5

Appendix A Emission Testing Requirements Crushing and Screening Equipment

ID		
No.	Equipment/Activity	Control Measure/Equipment
1	KPI Jaw Crusher	High Pressure Wet Suppression
2	JCI Cone Crusher	High Pressure Wet Suppression
3	JCI Cone Crusher	High Pressure Wet Suppression
4	Fab-Tech Aggregate Screen	High Pressure Wet Suppression
5	Fab-Tech Aggregate Screen	High Pressure Wet Suppression
6	Fab-Tech Aggregate Screen	High Pressure Wet Suppression
7	Haul Roads and Storage Piles	Wet suppression
8	Nonroad Engine – Caterpillar Generator Set (Caterpillar – 1,615 hp)	Ultra-low sulfur diesel

1. Equipment/Activity Identification

2. Approval Conditions

The following tables detail the specific requirements of this permit. In addition to the requirements listed below, equipment at this facility may be subject to other federal, state, and local regulations. The permit requirement number is identified in the left-hand column. The text of the permit requirement is contained in the middle column. The emission unit, equipment, or activity to which the permit requirement applies is listed in the right-hand column.

Emission Limits

Req. No.	Emiss	sion Limits		Equipment/ Activity ID No.
1.	Emissions from the rock crushing operations (crushing, screening, conveying, and haul roads) must not exceed any of the following:		1-7	
	Pollutant	Emission Limit		
	PM ₁₀ , total	1.40 ton/yr		
	PM _{2.5} , total	0.16 ton/yr		
	The long-term emission limits are 12-m Section 6 of the TSD for this Permit.	onth rolling sums calculated consisten	t with	
2.	Visible emissions from crushing, scree exceed 0% opacity for more than 3 min accordance with SWCAA Method 9 (Se	utes in any one hour period as determine		1-6
3.	Visible emissions from haul road traffic minutes in any one hour period as detern (See Appendix A of SWCAA 400). This equipment.	nined in accordance with SWCAA Met	thod 9	7

Req. No.	Emission Limits	Equipment/ Activity ID No.
4.	Visible emissions from diesel engines operating in support of crushing and screening operations must not exceed 10% opacity for more than 3 minutes in any one hour period as determined in accordance with SWCAA Method 9, except during periods of startup.	8
	For the purposes of this requirement, a startup period ends when the earlier of the following operating events occurs:(a) The engine has reached normal operating temperature; or(b) The engine has been operating for 15 minutes.	

Operating Limits and Requirements

Req. No.	Operating Limits and Requirements	Equipment/ Activity ID No.
5.	Reasonable precautions must be taken at all times to prevent and minimize fugitive emissions from plant operations.	Facility-wide
6.	The permittee must use recognized good practice and procedures to reduce odors to a reasonable minimum.	Facility-wide
7.	Wet suppression must be provided as necessary to control fugitive dust from haul roads, material storage piles, crushing and screening equipment, and material handling operations.	Facility-wide
8.	Each pollution control device/measure must be in use whenever the associated production equipment is in operation. Control devices must be operated and maintained in accordance with the manufacturer's specifications and operated in a manner that minimizes emissions.	1-8
9.	Emission units identified in this Permit must be maintained and operated in total and continuous conformity with the conditions identified in this Permit. SWCAA reserves the right to take any and all appropriate action to maintain the conditions of this Permit, including directing the facility to cease operations until corrective action can be completed.	1-8
10.	Each crusher and screen must be equipped with a high-pressure water spray system or other wet suppression system reviewed and approved in advance by SWCAA to provide equivalent or superior control of particulate matter emissions. Each high- pressure spray system must be capable of maintaining an operating pressure of 80 psig or greater during operation. A functional pressure gauge must be maintained onsite and a connection point provided for the purpose of demonstrating compliance with the minimum pressure requirement for high pressure spray systems.	1-6
11.	Spray/fog nozzles in the water spray systems for each rock crusher and aggregate screen must be visually inspected once per week when in operation to ensure proper function. Clogged or defective nozzles must be replaced or repaired prior to subsequent operation.	1-6
12.	Each diesel engine must be equipped with a non-resettable hour meter to record hours of operation.	8

Req. No.	Operating Limits and Requirements	Equipment/ Activity ID No.
13.	Each diesel engine must only be fired on fuel oil with a maximum sulfur content of 15 ppmw. Any fuel other than ultra-low sulfur fuel oil must be approved by	8
	SWCAA in writing prior to use.	

Monitoring and Recordkeeping Requirements

Req. No.	Monitoring and Recordkeeping	Requirements	Equipment/ Activity ID No.
14.	All air quality related complaints, including odd permittee and the results of any subsequent investi- be recorded for each occurrence.		Facility-wide
15.	With the exception of data logged by a computerize record required by this Permit must include the d making the record entry. If a control device or pr specific time period, a record must be made to that	ate and the name of the person cocess is not operating during a	1-8
16.	All records required by this Permit must be kept for than three years and must be maintained in a form by SWCAA representatives.	-	1-8
17.	Excess emissions and upset conditions must be rece	orded for each occurrence.	1-8
18.	 The following information must be collected, rec below, and maintained readily available on-site for (a) Hours of engine operation (b) Quantity and size of material crushed (c) Quantity of material screened (d) Type and length of haul roads (e) Quantity of vehicle miles travelled (f) Visual inspection of spray/fog nozzles (g) Maintenance of spray/fog nozzles (h) Equipment relocation (i) Sulfur content of fuel fired in diesel engines 	-	1-8

Emission Monitoring and Testing Requirements

Req. No.	Emission Monitoring and Testing Requirements	Equipment/ Activity ID No.
19.	An initial emission test must be conducted for all rock crushing equipment listed in this Permit subject to 40 CFR 60, Subpart OOO that has not been previously tested. Emission testing must be conducted no later than 60 days after achieving the maximum production rate and no later than 180 days after permit issuance. All emission testing must be conducted in accordance with Appendix A of this Permit and the requirements of 40 CFR 60, Subpart OOO. If an emission test meeting the requirements of 40 CFR 60 Subpart OOO has already been performed for a specific unit, submittal of the test report to SWCAA within the timeline described above satisfies this testing requirement.	1-6

Reporting Requirements

Req. No.	Reporting Requirements	Equipment/ Activity ID No.
20.	 All air quality related complaints received by the permittee must be reported to SWCAA within three days of receipt. Complaint reports must include the following information: (a) Date and time of the complaint; (b) Name of the complainant; (c) Nature of the complaint; and (d) Description of corrective action taken in response to complaint (if any). 	Facility-wide
21.	 Excess emissions must be reported to SWCAA as follows: (a) As soon as possible, but no later than 12 hours after discovery for emissions that represent a potential threat to human health or safety; (b) As soon as possible, but no later than 48 hours after discovery for emissions which the permittee wishes to claim as unavoidable pursuant to SWCAA 400-107; and (c) No later than 30 days after the end of the month of discovery for all other excess emissions. 	1-8
22.	The permittee must notify SWCAA at least 10 business days in advance of relocating approved equipment. The permittee must submit operational information (production quantities, hours of operation, location of nearest neighbor, etc.) sufficient to demonstrate that proposed operation will comply with the emission standards for a new source, and will not cause a violation of applicable ambient air quality standards.	1-8
23.	 The following emission-related information must be reported to SWCAA by March 15th for the previous calendar year: (a) Hours of engine operation; (b) Quantity and size of material crushed; (c) Quantity of material screened; (d) Quantity of vehicle miles travelled; and (e) Air emissions of criteria air pollutants, volatile organic compounds, toxic air pollutants (TAPs), and hazardous air pollutants (HAPs). 	1-8

Req. No.	Reporting Requirements	Equipment/ Activity ID No.
24.	Emission test results must be reported to SWCAA in writing within 45 days of test completion.	1-6

3. General Provisions

Req. No.	General Provisions
A.	For the purpose of ensuring compliance with this Permit, duly authorized representatives of the Southwest Clean Air Agency must be permitted access to the Permittee's premises and the facilities being constructed, owned, operated and/or maintained by the Permittee for the purpose of inspecting said facilities. These inspections are required to determine the status of compliance with this Permit and applicable regulations and to perform or require such tests as may be deemed necessary.
B.	The provisions, terms, and conditions of this Permit bind the Permittee, its officers, directors, agents, servants, employees, successors and assigns, and all persons, firms, and corporations acting under or for the Permittee.
C.	The requirements of this Permit survive any transfer of ownership of the source or any portion thereof.
D.	This Permit must be posted conspicuously at or be readily available near the source.
E.	This Permit will be invalidated, in whole or in part, if construction or installation of any new or modified equipment has not commenced within eighteen (18) months from date of issuance, if construction is discontinued for a period of eighteen (18) months or more without prior SWCAA approval, or if construction is not completed within a reasonable time.
F.	This Permit does not supersede requirements of other Agencies with jurisdiction and further, this Permit does not relieve the Permittee of any requirements of any other governmental Agency. In addition to this Permit, the Permittee may be required to obtain permits or approvals from other agencies with jurisdiction.
G.	Compliance with the terms of this Permit does not relieve the Permittee from the responsibility of compliance with SWCAA General Regulations for Air Pollution Sources, previously issued Regulatory Orders, RCW 70A.15, Title 173 WAC or any other applicable emission control requirements, nor from the resulting liabilities and/or legal remedies for failure to comply.
H.	If any provision of this Permit is held to be invalid, all unaffected provisions of the Permit will remain in effect and be enforceable.
I.	No change in this Permit will be made or be effective except as may be specifically set forth by written order of the Southwest Clean Air Agency upon written application by the Permittee for the relief sought.
J.	The Southwest Clean Air Agency may, in accordance with RCW 70A.15, impose such conditions as are reasonably necessary to assure the maintenance of compliance with the terms of this Permit, the Washington Clean Air Act, and the applicable rules and regulations adopted under the Washington Clean Air Act.

Req. No.	General Provisions
K.	For the purposes of establishing if a condition of this Permit has been violated or is being violated, nothing in this Permit precludes the use, including the exclusive use, of any credible evidence or information relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test procedures or methods had been performed.

Appendix A Emission Testing Requirements Crushing and Screening Equipment

1. Introduction:

The purpose of this performance testing requirement is to demonstrate compliance with the visual emissions limitations of this Permit and 40 CFR 60, Subpart OOO. This testing requirement is only applicable to rock crushing equipment that has not previously conducted initial emission testing pursuant to 40 CFR 60, Subpart OOO.

2. Testing Requirements:

- a. **Testing Schedule.** Emission testing must be performed within 60 days of achieving maximum production rate, but not later than 180 days after permit issuance for each affected facility that has not previously been tested consistent with the requirements of 40 CFR 60.8 and 60.675. If an affected facility is not in SWCAA's jurisdiction within this time frame or leaves SWCAA's jurisdiction within this time frame, emission testing must be conducted within 60 days of coming into, or returning to, SWCAA's jurisdiction.
- b. **Test Plan.** A comprehensive test plan must be submitted to SWCAA for review and approval at least 10 business days prior to each test. SWCAA personnel must be informed of the proposed test date and location at least 5 business days prior to testing so that a representative may be present during testing.
- c. **Test Location.** Visual observations must be made at each affected rock crusher, aggregate screen and conveyor transfer point associated with affected crushers and screens.
- d. Test Runs / Reference Methods. A minimum of 30 minutes of observations must be conducted as required by 40 CFR 60.675(c)(3) using the sampling method identified below.

Constituent	Reference Test Method
Opacity	EPA Method 9

3. Source Operation:

- a. A complete record of production related parameters including production rate, size of product being processed, startups, shutdowns, and adjustments must be kept during emissions testing to correlate operations with emissions and must be recorded in the test results report.
- b. Source operations during the emissions test must be representative of maximum intended operating conditions.

4. Reporting Requirements:

- a. Opacity observation data must be reduced and analyzed using the protocols in EPA Method 9 and SWCAA Method 9.
- b. Compliance must be determined by comparing the reduced opacity data with the visible emission limits contained in this Permit and 40 CFR 60, Subpart OOO.
- c. Unless otherwise directed by SWCAA, a final test report must be prepared and submitted in an approved electronic format to SWCAA within 45 calendar days of test completion and, at a minimum, must contain the following information:
 - (1) A description of the source including manufacturer, model number and design capacity of the equipment, and the location of the sample ports or test locations;
 - (2) Time and date of the test and identification and qualifications of the personnel involved;
 - (3) A summary of results, reported in units and averaging periods consistent with the applicable emission standard or limit;
 - (4) A summary of control system or equipment operating conditions;
 - (5) A summary of production related parameters cited in Section 3;
 - (6) A description of the test methods or procedures used including all field data, quality assurance/quality control procedures and documentation;
 - (7) A description of the analytical procedures used including all laboratory data, quality assurance/quality control procedures and documentation;
 - (8) Copies of field data and example calculations;
 - (9) Chain of custody information;
 - (10) Discussion of any abnormalities associated with the results; and
 - (11) A statement signed by the senior management official of the testing firm certifying the validity of the source test report.

5. Changes to Testing Requirements:

The emission test must be conducted as specified in the sections above. The Permittee may submit a written request to SWCAA for approval of minor modifications to the requirements above or to the testing schedule. Upon review of the request and in accordance with EPA delegation, SWCAA will inform the Permittee in writing of any approved modifications.